



Intrinsically Safe model 2425 DS

Product Profile

- Supports industry standard communications
- 2.4 GHz or 802.11b 11 Mbps radio
- Fast and easy integration options for terminal emulation or client/server
- Flexible connectivity choices
- Large, high contrast display
- Rugged casing

2 4 2 5 H A N D H E L D C O M P U T E R

The 2425 is the more ruggedized wireless model of the 2400 family hand-held line of data collection terminals. It is a cost-effective and reliable solution for collecting data in manufacturing, distribution and warehouse environments. An Intrinsically Safe model provides protection in hazardous areas containing gas, vapors and dust.

For fast and easy implementation, the 2425 integrates with common host environments using standard protocols. Configure the 2425 with TCP/IP for a direct connection to your Ethernet or Token

Ring LAN or connect to Ethernet and IBM networks through the DCS 300 Server, which also provides guaranteed host connection and network management services.

With a contoured shape and centered scan button, the 2425 is comfortable to use in either hand. The large display provides enough space for menus, help screens or even graphics. It is tilted to improve readability while scanning, and the alphanumeric keyboard provides tactile feedback with the frequently used numeric keys oversized for easier input.

Physical Characteristics**Length:** 26.9 cm (10.6")**Height:** 7.1 cm (2.8") at scanner, 5.7 cm (2.3") at grip**Width:** 8.2 cm (3.2") at scanner, 6.4 cm (2.5") at grip**Weight:** 766 g (27 oz.) including battery**Environment****Operating:** -20° to 50°C (-4° to 122°F)**Storage:** -20° to 60°C (-4° to 140°F)**Humidity:** Non-condensing (0 to 95% RH)**Shock and Vibration Protection:**

Warranted for 5-foot drop to concrete

Meets MIL-STD 28800E

Power**Operating:** Lithium Ion battery pack**Memory Backup:** Rechargeable NiCad**Memory****RAM Memory:** 1MB**Non-volatile Flash Memory:** 2MB

Option for 2MB additional, 4 MB total

Interfaces

- Optical Serial Interface
- RS232-C up to 38.4 baud
- XMODEM, YMODEM for data transfer

Display

- CGA compatible backlit LCD displaying 16 lines of 20 characters per line (160 x 128 dot matrix) plus graphic status icons

Keyboard

- Elastomeric 56-key with full alphanumeric set, function keys and oversized numeric
- Options for U.S., Multilingual European, IBM 5250, IBM 3270 and VT/ANSI layouts

Software**Programmable:** Microsoft® C/C++, EzBuilder**Terminal Emulation:** IBM 3270 and

5250 SNA and TELNET; ANSI/VT 100, 220, 320

TELNET; Screen mapping

Web-based: dcBrowser™ for HTML applications**North America**

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

Europe/Middle East & Africa

Headquarters
Sovereign House
Vestern Road
Reading RG1 8BT
United Kingdom
tel: 44.118.987.9400
fax: 44.118.987.9401

Asia

Asia Regional Office
26-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.6324.8391
fax: 65.6324.8393

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
118 Jian Guo Road
Chaoyang District, Beijing 100022
Tel: 86 10.5165.5922
Fax: 86 10.6567.6778

Connectivity

- Direct TCP/IP Support
- DHCP Client
- Sockets interface or terminal emulation

Bar Code Symbolologies

Code 39, 2 of 5, Interleaved 2 of 5, Codabar, UPC/EAN Code 128, Code 11, Code 93, Plessey, MSI, Code, PDF-417 (non I-Safe Version only)

Bar Code Scanning Options

Integrated visible laser diode scanner

USA/Canada Class II, International Class 2

Depth of Field*—Standard Range (670nm)

5 mil	9.4-15.7cm	3.7-6.2"
10 mil	7.4-35.3cm	2.9-13.9"
20 mil	10.2-63.5cm	4-25"
30 mil	10.2-86.4cm	4-34"
40 mil	12.7-99cm	5-39"
55 mil	19.1-126cm	7.5-49"
55 mil retroreflective	105-151cm	41-59"
100 mil retroreflective	113-227cm	44-89"

Depth of Field*—Long Range (650nm)

5 mil	29.5-49.8cm	11.6-19.6"
10 mil	21.8-85.3cm	8.6-33.6"
20 mil	21.8-98cm	8.6-38.6"
30 mil	24.4-192cm	9.6-75.6"
40 mil	24.4-204.7cm	9.6-80.6"
70 mil retroreflective	192-410.5cm	76.6-161.6"
100 mil retroreflective	212.3-532.4cm	83.6-209.6"

*Measured for Code 39

- High Density, High Performance and PDF 417 options available (non I-Safe version only)
- Optional adapter module for use with cabled scanners and wands (non I-Safe version only)

Integrated RF Module**Frequency:** 2.4 GHz frequency band, actual frequencies in use vary by country**WLI Forum OpenAir****Type:** Frequency Hopping Spread Spectrum**Data Rate:** 1.6 Mbps, .8 Mbps fallback**Range*:** From 1500+ ft (450+ m) to 500 ft (150 m) depending on environment**IEEE 802.11b Wi-Fi Certified****Type:** Direct Sequence Spread Spectrum**Data Rate:** 11/5.5/2/1 Mbps with Auto fallback for increased range**Australia**

Level 7, 200 Pacific Highway
Crowns Nest, NSW 2065
Australia
tel: 61.2.9492.4400
fax: 61.2.9954.6300

South America & Mexico

Intermec South America Ltda.
Rua Samuel Morse 120 9 andar
Brooklin CEP04576-060
São Paulo, SP
Brazil
tel: 55.11.5502.6770

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
Col. Hipodromo Condesa
Mexico, DF, 06140 Mexico
tel: 525.55.241.4800
fax: 525.55.211.8121

Range* at 1 Mbps: From 1750 ft (533 m) to 165 ft (50 m) depending on environment**Range* at 11 Mbps:** From 525 ft (160 m) to 80 ft (24 m) depending on environment**Security:** Wired Equivalent Privacy (WEP) - 64 or 128 bit encryption

*Unlimited range with roaming

Host Support via DCS 300 Server**Host Environment:** IBM AS 400, S/390, Digital, HP, UNIX, Windows NT**Connectivity:** Ethernet, Token Ring, 100BASET, Twinax, Coax, SDLC**Communications:** TCP/IP, SNA**Accessories**

Handstrap, holster, belt clip, pistol grip handle, vehicle mount holder, battery charger, battery pack, serial adapter and communications dock, User manuals, Programmer's Software Kit (PSK)

Regulatory Approvals

UL Listed, UL 1950 and C22.2 No. 950, TÜV GS Licensed, EN 60950 and EN 60825-1, FCC Part 15, Canada, RSS210 and ICES-003 Class B, EN 55022 / CISPR 22, Class B, ETS 300 328, ETS 300 826, Compliant with all European directives, CE marked

Intrinsically Safe Model 2425 DS

Please contact your Intermec representative for configurations available

Regulatory Approvals

UL Listed, UL 913 and C22.2 No. 157 Division 1: Class I - Groups C & D

UL Listed UL 1604 & C22.2 #213 Division 2, Class I Groups A, B, C & D

UL Listed UL 1604 only Division 2, Class II Groups F & G

SIRA Certified to CENELEC EN 50020 and ATEX Directive. Rated EEx ia 11b T4

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

**Internet**

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A.
608456-01F 07/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Intermec
e x p e c t **MORE**