

Product Profile



- Intermec Designed & Manufactured
- Dual high capacity Lithium Ion batteries
- Intermec SmartSystem™ Device Management
- Serial, USB and Class 1 Bluetooth™ Interfaces Standard
- Integrated RFID chip for asset management and servicing
- Frontloading batteries
- Flexibility to use roll or fanfold receipt paper
- High visibility buttons and indicators
- International logos facilitate global use
- Simple paper installation
- Operate in temperatures as low as -20° C

P B 4 2 P O R T A B L E P R I N T E R

Intermec's PB42 four inch wireless portable receipt printer is designed to improve direct store delivery (DSD), Field Service, and Home Utility applications. The PB42 printer interfaces seamlessly with the CK60 and 700 Intermec handheld computers. Daily route activities are easily entered and tracked via a mobile computer throughout a workers shift. Receipts are immediately provided to the customer for prompt payment or to eliminate duplicate billing efforts.

The unique Intermec design of the PB42 portable receipt printer ensures ease of use. This is very important for delivery drivers who negotiate routes with multiple stops and rugged conditions. Special design features include sharing of battery design with the CK60 mobile computer, simple receipt paper installation, high visibility buttons and indicators to show when the printer is within radio range or when the lithium

ion batteries are getting low. Charge up to four printers at once with the unique four bay charger. Printers "drop-in" and charge from hinge pins; no charge cable required. Frontloading batteries that can be removed with just one hand. Lexan® media windows conveniently show media status. Standard belt clip & wrist strap also add to the convenience of operation.

The PB42 printer has an integrated Ready-to-Work™ light. This is part of the Intermec SmartSystem™ and provides a visual cue to the operating state of the printer.

Intermec's PB42 portable receipt printer is ideal for use worldwide. The PB42 printer features widely recognized international logo indicators on the buttons, multiple language character sets, and worldwide certifications. The PB42 printer is ideal for streamlining processes and route deliveries in DSD, field service, and home utility industries worldwide.

Application

Thermal receipt printing

Physical Characteristics

Depth: 3.1 inches (7.87 cm)

Height: 7.1 inches (18.03 cm)

Width: 6.62 inches (16.82 cm)

Weight: 3.0 lb (1.36 kg) w/ 2 battery

packs and full roll receipt paper

Drop test: 4 ft to concrete

Print Specifications

Print Width: 4.1 inch (104 mm)

Element Size: 0.0049 inch (0.125mm)

Minimum graphical element: 0.010 inch (0.254 mm)

Print Speed

3 ips (80 mm/sec)

Print Resolution

203 DPI (8 dots/mm)

Receipts

Max. Width: 4.4 inch (111.8 mm)

Thickness: 0.002 to .0044 inch (0.05 to 0.112 mm)

Tracking: Center

Style: Roll-fed or fanfold

Label Roll max diameter: 2.65 inches (67 mm)

Label Roll Core ID: .75 inch (19.05 mm)

Media Type: Receipt paper

Standard Interface

- Serial RS-232 (115 kbps)
- USB v.1.1
- Class 1 Bluetooth™

Optional Interface

- BlueTooth™ Class 1 - range up to 100 m (328 feet)
- 802.11b /g – range up to 100 m (328 feet)

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies
9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

Canada

7065 Tranmere Drive
Mississauga, Ontario
L5S 1M2 Canada
tel: 905.673.9333
fax: 905.673.3974

**Europe/
Middle East & Africa**

Headquarters
Sovereign House
Vestern Road
Reading RG1 8BT
United Kingdom
tel: 44.118.987.9400
fax: 44.118.987.9401

Asia

Asia Regional Office
26-16 International Plaza
10 Anson Road
Singapore 079903
tel: 65.6324.8391
fax: 65.6324.8393

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
118 Jian Guo Road
Chaoyang District, Beijing 100022
Tel: 86 10.5165.5922
Fax: 86 10.6567.6778

Symbologies

Int 2 of 5, Codabar, EAN-128, PDF-417,
UPC-A, Code 128, EAN13, EAN08, Code 39,
New GTIN

Character Sets

- West European or Latin No. 1 and 9 for the following languages: Danish, Dutch, English, Faeroese, Finnish, French, German, Icelandic, Irish, Italian, Norwegian, Portuguese, Spanish, and Swedish.
- East European or Latin No. 2 for the following languages: Albanian, Czech, English, German, Hungarian, Polish, Rumanian, Serbocroatian, Slovak, and Slovene.
- Cyrillic for the following languages: Bulgarian, Byelorussian, English, Macedonian, Russian, Serbocroatian, and Ukrainian.
- Latin / Arabic
- Latin / Greek
- Latin / Hebrew
- U.S. standard
- Europe multilingual
- Code Page requirements for Far East
 - Thai extended
 - Simplified Chinese (GB2312)
 - Traditional Chinese (Big5)
 - Japanese
- Korean_Wansung

Font types

40 column, normal, bold, 80 column, normal, bold, 132 column, normal, bold

Standard Memory

- 16 MB SDRAM
- 4 MB Flash

Australia

Level 7, 200 Pacific Highway
Crowns Nest, NSW 2065
Australia
tel: 61.2.9492.4400
fax: 61.2.9954.6300

South America & Mexico

Intermec South America Ltda.
Rua Samuel Morse 120 9 andar
Brooklin CEP04576-060
São Paulo, SP
Brazil
tel: 55.11.5502.6770

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
Col. Hipodromo Condesa
Mexico, DF, 06140 Mexico
tel: 525.55.241.4800
fax: 525.55.211.8121

LED Indicators

- Ready-to-Work™ – Blue
- Radio – Green Flashing
- Battery – Green/Red

Power Supply

AC Adapter: 50 Watt

Voltage Range: 12 V ± 5%.

Rechargeable Li-Ion Battery: 7.2V, 2.4A-H. Each printer ships standard with two batteries.

Operating Environment

Operating: -20°C (-4°F) to 50°C (122°F)

Non-operating: -30°C (-22°F) to 70°C (158°F)

Battery Charging: 0°C (32°F) to 50°C (122°F)

Relative Humidity: 10% to 90% non-condensing

Regulatory Approvals

North America UL and cUL Listed, UL 60950; Europe TÜV Rheinland GS Licensed, EN 60950; Mexico NYCE CERTIFIED, NOM 19; China CCC Certified; Other Countries EN 60950 CB

EMC Approvals

USA FCC Title 47, Part 15, Subpart B, Class B; Europe EMC Directive (EN 55022 Class B + EN 55024); CISPR22; China CCC CE (EN55022 Class A), FCC Class A, UL, CSA, C-Tick

Options & Accessories

Belt Clip, Shoulder Strap, Batteries, AC Charger, Vehicle Mount, External Paper Tray, AC Power Adapter, Cigarette Lighter Adapter, Nylon System Case, Four Bay Printer Charger

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611578-01D 07/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Intermec[®]
e x p e c t **MORE**[®]